

MATERIAL SAFETY DATA SHEET

2-(2-BUTOXYETHOXY)-ETHANOL

MSDS Name:	2-(2-BUTOXYETHOXY)-ETHANOL, 99+%
Synonyms:	
Company Identification: (INDIA)	Veritas House, 70 Mint Road, Fort, Mumbai - 400 001. INDIA
For information in the INDIA, call:	Tel: +91 - 22 - 2275 5555 / 6184 0000, Fax: +91 - 22 - 2275 5556 / 6184 0001

Section 2 - Composition, Information on Ingredients

CAS#	Chemical Name:	%	EINECS#
112-34-5	2-(2-BUTOXYETHOXY)-ETHANOL	99+%	203-961-6

Hazard Symbols:	XI
	
Risk Phrases:	36

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Irritating to eyes.

Potential Health Effects

Eye:	Causes eye irritation.
Skin:	May cause skin irritation.
Ingestion:	The toxicological properties of this substance have not been fully investigated.
Inhalation:	Effects may be delayed. Causes delayed lung injury. Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. May cause severe allergic respiratory reaction.
Chronic:	

Section 4 - First Aid Measures

Eyes:	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin:	Get medical aid. Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Ingestion:	Get medical aid. Wash mouth out with water.
Inhalation:	Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.
Notes to Physician:	

Section 5 - Fire Fighting Measures

General Information:	As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. May form explosive peroxides.
Extinguishing Media:	In case of fire, use water, dry chemical, chemical foam, or alcohol-resistant foam.

Section 6 - Accidental Release Measures

General Information:	Use proper personal protective equipment as indicated in Section 8.
Spills/Leaks:	Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container.

Section 7 - Handling and Storage

Handling:	Avoid breathing dust, vapor, mist, or gas. Avoid contact with skin and eyes.
Storage:	Store in a cool, dry place. Store in a tightly closed container. May form explosive peroxides on prolonged storage.

Section 8 - Exposure Controls, Personal Protection

Engineering Controls:	
	Use adequate ventilation to keep airborne concentrations low.
Exposure Limits	
	CAS# 112-34-5:
	Germany: 100 mg/m ³ TWA
	Netherlands: 9 ppm MAC; 50 mg/m ³ MAC
	Spain: 100 mg/m ³ VLA-ED

Personal Protective Equipment

Eyes:	Wear safety glasses and chemical goggles if splashing is possible.
Skin:	Wear appropriate protective gloves and clothing to prevent skin exposure.
Clothing:	Wear appropriate protective clothing to minimize contact with skin.
Respirators:	Wear a NIOSH/MSHA or European Standard EN 149 approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

Section 9 - Physical and Chemical Properties

Physical State:	Clear liquid
Color:	APHA: 10 max
Odor:	characteristic odor - faint odor - mild odor
pH:	Not available
Vapor Pressure:	.01 mm Hg @ 20 deg C
Viscosity:	6.16 mPa.s 20 deg C
Boiling Point:	231 deg C @ 760.00mm Hg
Freezing/Melting Point:	0 deg C
Autoignition Temperature:	227 deg C
Flash Point:	78 deg C
Explosion Limits: Lower:	.07 vol %
Explosion Limits: Upper:	5.30 vol %
Decomposition Temperature:	Not available
Solubility in water:	Soluble
Specific Gravity/Density:	0.955

Molecular Formula:	C8H18O3
Molecular Weight:	162.23

Section 10 - Stability and Reactivity

Chemical Stability:	Not available
Conditions to Avoid:	Incompatible materials.
Incompatibilities with Other Materials	Strong oxidizing agents.
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide.
Hazardous Polymerization	Has not been reported.

Section 11 - Toxicological Information

RTECS#:	CAS# 112-34-5: KJ9100000
LD50/LC50:	RTECS: CAS# 112-34-5: Draize test, rabbit, eye: 20 mg Severe; Draize test, rabbit, eye: 20 mg/24H Moderate; Oral, mouse: LD50 = 2400 mg/kg; Oral, mouse: LD50 = 6050 mg/kg; Oral, rabbit: LD50 = 2200 mg/kg; Oral, rat: LD50 = 5660 mg/kg; Oral, rat: LD50 = 4500 mg/kg; Skin, rabbit: LD50 = 2700 mg/kg;.
Carcinogenicity:	2-(2-BUTOXYETHOXY)-ETHANOL - Not listed as a carcinogen by ACGIH, IARC, NTP, or CA Prop 65.
Other:	The toxicological properties have not been fully investigated. See actual entry in RTECS for complete information.

Section 12 - Ecological Information

Not available

Section 13 - Disposal Considerations

Dispose of in a manner consistent with federal, state, and local regulations.

Section 14 - Transport Information

	IATA	IMO	RID/ADR
Shipping Name:	Not available	Not available	Not available
Hazard Class:			
UN Number:			
Packing Group:			

Section 15 - Regulatory Information

European/International Regulations
European Labeling in Accordance with EC Directives
Hazard Symbols: XI
Risk Phrases:
➤ R 36 Irritating to eyes.
Safety Phrases:
➤ S 24 Avoid contact with skin.
➤ S 26 In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
WGK (Water Danger/Protection)
➤ CAS# 112-34-5: 1
Canada

- CAS# 112-34-5 is listed on Canada's DSL List

US Federal

- TSCA
- CAS# 112-34-5 is listed on the TSCA Inventory.

Section 16 - Other Information

MSDS Creation Date:	July 24, 2015
Revision #0 Date	

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages howsoever arising, even if the company has been advised of the possibility of such damages.